

Amendments to the Claims:

This listing of claims will replace all prior version, and listings, of claims in the application:

Listing of Claims:

1. (currently amended) An apparatus comprising:

a key generator to generate an operating system nub key (OSNK) unique to an operating system (OS) nub, the OS nub being part of an operating system ~~running to run~~ on a secure platform; and

a usage protector coupled to the key generator to protect usage of a subset of a software environment using the ~~OSNK~~ OSNK;

wherein the usage protector performs at least one operation selected from the group consisting of:

encrypting a value while operating in isolated execution mode; and

decrypting an encrypted value while operating in isolated execution mode.

2. (original) The apparatus of claim 1 wherein the key generator comprises:

a combiner to combine an identification of the OS nub and a master binding key (BK0) of the secure platform, the combined identification and the BK0 corresponding to the OSNK.

3. (currently amended) The apparatus of claim 2 wherein the identification is

comprises a hash value of one of an item selected from the group consisting of the OS nub and a certificate representing the OS nub.

4. (original) The apparatus of claim 1 wherein the usage protector comprises:
 - an encryptor to encrypt the subset of the software environment using the OSNK, the encrypted subset being stored in a storage; and
 - a decryptor to decrypt the encrypted subset using the OSNK, the encrypted subset being retrieved from the storage.

5. (original) The apparatus of claim 1 wherein the usage protector comprises:
 - an encryptor to encrypt a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;
 - a decryptor to decrypt the encrypted first hash value using the OSNK, the encrypted first hash value being retrieved from the storage; and
 - a comparator to compare the decrypted first hash value to a second hash value to generate a compared result, the compared result indicating whether the subset of the software environment has been modified.

6. (original) The apparatus of claim 1 wherein the usage protector comprises:
 - a first encryptor to encrypt a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;
 - a second encryptor to encrypt a second hash value using the OSNK; and
 - a comparator to compare the encrypted second hash value to the encrypted first hash value to generate a compared result, the encrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

7. (original) The apparatus of claim 1 wherein the usage protector comprises:

a decryptor to decrypt a protected private key to generate a private key using the OSNK;

a signature generator coupled to the decryptor to generate a signature of the subset of the software environment using the private key, the signature being stored in a storage; and

a signature verifier to verify the signature to generate a modified/not modified flag using a public key, the signature being retrieved from the storage, the modified/not modified flag indicating whether the subset has been modified.

8. (original) The apparatus of claim 1 wherein the usage protector comprises:

a manifest generator to generate a manifest of the subset of the software environment, the manifest describing the subset of the software environment, the manifest being stored in a storage;

a signature generator coupled to the manifest generator to generate a manifest signature using a private key, the private key being decrypted by a decryptor using the OSNK, the manifest signature being stored in the storage;

a signature verifier to verify the manifest signature to generate a signature verified flag using a public key, the manifest signature being retrieved from the storage; and

a manifest verifier to verify the manifest to generate a manifest verified flag, the manifest being retrieved from the storage, the manifest verified flag and the signature verified flag being tested at a test center, the test center generating a pass/fail signal to indicate whether the subset has been modified.

9. (canceled)

10. (currently amended) The apparatus of claim 1 wherein the software environment ~~is one of~~ comprises an operating system selected from the group consisting of a Windows operating system, a Windows 95 operating system, a Windows 98 operating system, a Windows NT operating system, and a Windows 2000 operating system.

11. (original) The apparatus of claim 1 wherein the subset of the software environment is a registry of an operating system.

12. (original) The apparatus of claim 2 wherein the BK0 is generated at random on a first invocation of a processor nub.

13. (currently amended) A method comprising:

generating an operating system nub key (OSNK) unique to an operating system (OS) nub, the OS nub being part of an operating system ~~running~~ to run in a software environment on a secure platform; and

protecting usage of a subset of the software environment using the ~~OSNK~~ OSNK;

wherein the operation of protecting usage of a subset of the software environment comprises at least one operation selected from the group consisting of:
encrypting a value while operating in isolated execution mode; and
decrypting an encrypted value while operating in isolated execution mode.

14. (currently amended) The method of ~~claim 14~~ claim 13 wherein generating the OSNK comprises:

combining an identification of the OS nub and a master binding key (BK0) of the secure platform, the combined identification and the BK0 corresponding to the OSNK.

15. (currently amended) The method of claim 14 wherein the identification is comprises a hash value of one of an item selected from the group consisting of the OS nub and a certificate representing the OS nub.

16. (original) The method of claim 13 wherein protecting usage comprises:

encrypting the subset of the software environment using the OSNK;
storing the encrypted subset in a storage; and
decrypting the encrypted subset from the storage using the OSNK.

17. (original) The method of claim 13 wherein protecting usage comprises:

encrypting a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

decrypting the encrypted first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being retrieved from the storage; and

comparing the decrypted first hash value to a second hash value to generate a compared result, the decrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

18. (original) The method of claim 13 wherein protecting usage comprises:

encrypting a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

encrypting a second hash value using the OSNK; and

comparing the encrypted first hash value to the encrypted second hash value to generate a compared result, the encrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

19. (original) The method of claim 13 wherein protecting usage comprises:

decrypting a protected private key to generate a private key using the OSNK;

generating a signature of the subset of the software environment using the private key, the signature being stored in a storage; and

verifying the signature to generate a modified/not modified flag using a public key, the signature being retrieved from the storage, the modified/not modified flag indicating whether the subset of the software environment has been modified.

20. (original) The method of claim 13 wherein detecting comprises:

generating a manifest of the subset of the software environment, the manifest describing the subset of the software environment, the manifest being stored in a storage;

generating a manifest signature of the manifest using a private key, the private key being decrypted using the OSNK, the manifest signature being stored in the storage;

verifying the manifest signature to generate a signature verified flag using a public key, the manifest signature being retrieved from the storage; and

verifying the manifest to generate a manifest verified flag, the manifest being retrieved from the storage, the manifest verified flag and the signature verified flag being tested at a test center, the test center generating a pass/fail signal, the pass/fail signal indicating whether the subset of the software environment has been modified.

21. (canceled)

22. (currently amended) The method of claim 13 wherein the software environment ~~is one of~~ comprises an operating system selected from the group consisting of a Windows operating system, a Windows 95 operating system, a Windows 98 operating system, a Windows NT operating system, and a Windows 2000 operating system.

23. (original) The method of claim 13 wherein the subset of the software environment is a registry of the operating system.

24. (original) The method of claim 14, wherein the BK0 is generated at random on a first invocation of a processor nub.

25. (currently amended) A computer program product comprising:

a computer usable medium having computer program code embodied therein, the computer program product having:

computer readable program code ~~for generating~~ to generate an operating system nub key (OSNK) unique to an operating system (OS) nub, the OS nub being part of an operating system ~~running~~ to run in a software environment on a secure platform; and

computer readable program code ~~for protecting~~ to protect usage of a subset of the software environment using the ~~OSNK~~ OSNK;

wherein the operation of protecting usage of a subset of the software environment comprises at least one operation selected from the group consisting of: encrypting a value while operating in isolated execution mode; and decrypting an encrypted value while operating in isolated execution mode.

26. (original) The computer program product of claim 25 wherein the computer readable program code for generating the OSNK comprises:

computer readable program code for combining an identification of the OS nub and a master binding key (BK0) of the secure platform, the combined identification and the BK0 corresponding to the OSNK.

27. (currently amended) The computer program product of claim 26 wherein the identification is comprises a hash value of ~~one of~~ an item selected from the group consisting of the OS nub and a certificate representing the OS nub.

28. (original) The computer program product of claim 25 wherein the computer readable program code for protecting usage comprises:

computer readable program code for encrypting the subset of the software environment using the OSNK;

computer readable program code for storing the encrypted subset; and

computer readable program code for decrypting the encrypted subset from the storage using the OSNK.

29. (original) The computer program product of claim 25 wherein the computer readable program code for protecting usage comprises:

- computer readable program code for encrypting a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

- computer readable program code for decrypting the encrypted first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being retrieved from the storage; and

- computer readable program code for comparing the decrypted first hash value to a second hash value to generate a compared result, the decrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

30. (original) The computer program product of claim 25 wherein the computer readable program code for protecting usage comprises:

- computer readable program code for encrypting a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

- computer readable program code for encrypting a second hash value using the OSNK; and

- computer readable program code for comparing the encrypted first hash value to the encrypted second hash value to generate a compared result, the encrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

31. (original) The computer program product of claim 25 wherein the computer readable program code for protecting usage comprises:

computer readable program code for decrypting a protected private key to generate a private key using the OSNK;

computer readable program code for generating a signature of the subset of the software environment using the private key, the signature being stored in a storage; and

computer readable program code for verifying the signature to generate a modified/not modified flag using a public key, the signature being retrieved from the storage, the modified/not modified flag indicating whether the software environment has been modified.

32. (original) The computer program product of claim 25 wherein the computer readable program code for protecting usage comprises:

computer readable program code for generating a manifest of the subset of the software environment, the manifest being stored in a storage;

computer readable program code for generating a manifest signature of the manifest using a private key, the private key being decrypted using the OSNK, the manifest signature being stored in the storage;

computer readable program code for verifying the manifest signature to generate a signature verified flag using a public key, the manifest signature being retrieved from the storage; and

computer readable program code for verifying the manifest to generate a manifest verified flag , the manifest being retrieved from the storage, the manifest verified flag and the signature verified flag being tested at a test center, the test center generating a pass/fail signal, the pass/fail signal indicating whether the subset of the software environment has been modified.

33. (canceled)

34. (currently amended) The computer program product of claim 25 wherein the software environment ~~is one of~~ comprises an operating system selected from the group consisting of a Windows operating system, a Windows 95 operating system, a Windows 98 operating system, a Windows NT operating system, and a Windows 2000 operating system.

35. (original) The computer program product of claim 25 wherein the subset of the software environment is a registry of an operating system.

36. (original) The computer program product of claim 26 wherein the BK0 is generated at random on a first invocation of a processor nub.

37. (currently amended) A system to provide a secure platform, the system comprising:

a processor;

a storage device coupled to the processor, the storage storing a subset of a software environment to run on the secure platform; and

a usage protector comprising:

a key generator to generate an operating system nub key (OSNK) unique to an operating system (OS) nub, the operating system nub being part of ~~[[a]]~~ the software environment ~~running on a secure platform~~; and

a usage protector coupled to the key generator to protect usage of a subset of the software environment using the ~~OSNK~~ OSNK;

wherein the operation of protecting usage of a subset of the software environment comprises at least one operation selected from the group consisting of:

encrypting a value while operating in isolated execution mode; and

decrypting an encrypted value while operating in isolated execution mode.

38. (original) The system of claim 37 wherein the key generator comprises:

a combiner to combine an identification of the operating system nub and a master binding key (BK0) of the secure platform, the combined identification and BK0 corresponding to the OSNK.

39. (currently amended) The system of claim 38 wherein the identification is comprises a hash value of ~~one of~~ an item selected from the group consisting of the OS nub and a certificate representing the OS nub.

40. (original) The system of claim 37 wherein the usage protector comprises:

an encryptor to encrypt the subset of the software environment using the OSNK, the encrypted subset being stored in a storage; and

a decryptor to decrypt the encrypted subset using the OSNK, the encrypted subset being retrieved from the storage.

41. (original) The system of claim 37 wherein the usage protector comprises:

- an encryptor to encrypt a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

- a decryptor to decrypt the encrypted first hash value using the OSNK, the encrypted first hash value being retrieved from the storage; and

- a comparator to compare the decrypted first hash value to a second hash value to generate a compared result, the compared result indicating whether the subset of the software environment has been modified.

42. (original) The system of claim 37 wherein the usage protector comprises:

- a first encryptor to encrypt a first hash value of the subset of the software environment using the OSNK, the encrypted first hash value being stored in a storage;

- a second encryptor to encrypt a second hash value using the OSNK; and

- a comparator to compare the encrypted second hash value to the encrypted first hash value to generate a compared result, the encrypted first hash value being retrieved from the storage, the compared result indicating whether the subset of the software environment has been modified.

43. (original) The system of claim 37 wherein the usage protector comprises:

- a decryptor to decrypt a protected private key to generate a private key using the OSNK;

- a signature generator coupled to the decryptor to generate a signature of the subset of the software environment using the private key, the signature being stored in a storage; and

- a signature verifier to verify the signature to generate a modified/not modified flag using a public key, the signature being retrieved from the storage, the modified/not modified flag indicating whether the subset of the software environment has been modified.

44. (original) The system of claim 37 wherein the usage protector comprises:

a manifest generator to generate a manifest of the subset of the software environment, the manifest describing the subset of the software environment, the manifest being stored in a storage;

a signature generator coupled to the manifest generator to generate a manifest signature of the manifest using a private key, the private key being decrypted using the OSNK, the manifest signature being stored in the storage;

a signature verifier to verify the manifest signature to generate a signature verified flag using a public key, the manifest signature being retrieved from the storage; and

a manifest verifier to verify the manifest to generate a manifest verified flag, the manifest being retrieved from the storage, the manifest verified flag and the signature verified flag being tested by a test center, the test center generating a pass/fail signal indicating whether the subset has been modified.

45. (canceled)

46. (currently amended) The system of claim 37 wherein the software environment ~~is one of~~ comprises an operating system selected from the group consisting of a Windows operating system, a Windows 95 operating system, a Windows 98 operating system, a Windows NT operating system, and a Windows 2000 operating system.

47. (original) The system of claim 37 wherein the subset of the software environment is a registry of an operating system.

48. (original) The system of claim 38 wherein the BK0 is generated at random on a first invocation of a processor nub.

Amendments to the Drawings:

The attached replacement sheet of drawings includes changes to FIG. 3E. In FIG. 3E, reference number 365 has been changed to 311, to correct an inadvertent duplication of reference numbers.